SUNNYWAY

SWE019

PN: SW19049EB56



Sunnyway Technology

Add: Building 65-302, No.421 Hongcao Road, Xuhui District, Shanghai
Tel: +86-021-6484 2326 Fax: +86-021-6484 2328
Email: sales@sunny-way.com Web: www.sunny-way.com

1. Electrical Specifications


Standards	ISM-915MHz
Frequency range (MHz)	915MHz
Peak Gain (dBi)	0.44dBi
Average Gain (dB)	-3.46dB
VSWR	1.52
Return Loss	-13.62
Efficiency (%)	45.11%
Polarization mode	Linear
Radiation pattern	Omni-Directional
Output impedance (Ω)	50
Max. Input Power(W)	25

2. Mechanical and Environmental Specification


Mounting Type	Connector Mount
Connector Type	SMA
Antenna size(mm)	47.3mm*φ8.5mm
Material	ABS
Operating Temperature (˚C)	- 40 ˚C ~ + 85 ˚C
Storage Temperature(˚C)	- 40 ˚C ~ + 85 ˚C

3. Antenna parameters


FRE（MHz）	915
VSWR	1.52
Return Loss	-13.62
Eff (%)	45.11
Average Gain(dB)	-3.46




VSWR




Return Loss



914.00MHz - 916.00MHz Gain
5.00
3.00
1.00
-1.00
-3.00
-5.00
914.00
915.00
916.00


914.00MHz - 916.00MHz Efficiency
50.00
48.00
46.00
44.00
42.00
40.00
914.00
915.00
916.00

Directional pattern



4. Antenna Drawings



Series	Component name	Specification	Color	Quantity
2	SMA	SMA-J	white	1
1	noumenon	ABS	black	1