finder
RELAYING INNOVATION

Modular contactors
25 - 32 - 40 - 63 A

- Hotel room energy-enabling units
- Garden and night lighting
- Streetlights and car park lighting
- Bathrooms lighting control
- Office lighting control
- Pump control



22
SERIES

Prices, features, specifications, capabilities, appearance and availability of our products and services are subject to change without notice.
FINDER assumes no responsibility for the presence of possible errors or insufficient information in this document.
In case of discrepancies between the printed and online versions, the latter prevails.

25 A modular contactor - 2 pole

- 17.5 mm wide
- NO contact gap ≥ 3 mm, double break
- Continuous duty for the coil and contacts
- AC/DC silent coil (with varistor protection)
- Protective separation (reinforced insulation) between coil and contacts
- Mechanical and LED indicators as standard
- Auto-On-Off selector version available
- AgNi and $AgSnO_2$ contact versions available
- Compliant with EN 61095: 2009
- Auxiliary contact module available, quick-assembly with the main contactor (1 NO + 1 NC and 2 NO versions)
- For railway applications; materials compliant with fire and smoke characteristics (EN 45545-2 + A1: 2016)
- 35 mm rail (EN 60715) mount

22.32
Box clamp



For outline drawings see page 14

	22.32.0.xxx.1xx0	22.32.0.xxx.4xx0
		
	• AgNi contacts, specifically intended for resistive and slightly inductive loads as well as for motor loads	• $AgSnO_2$ contacts, specifically intended for lamp loads and for high inrush current loads
	 2 NO (x3x0)	 1 NO + 1 NC (x5x0)
	 2 NC (x4x0)	

Contact specification			
Contact configuration		2 NO, 3 mm* (or 1 NO + 1 NC or 2 NC)	
Rated current/Maximum peak current	A	25/80	25/120
Rated voltage	V AC	250/440	250/440
Rated load AC1 / AC-7a (per pole @ 250 V)	VA	6250	6250
Rated current AC3 / AC-7b	A	10	10
Rated load AC15 (per pole @ 230 V)	VA	1800	1800
Single-phase motor rating (230 V AC)	kW	1	1
Rated current AC-5a (per pole @ 250 V)	A	15	15
Rated current AC-7c	A	—	10
Nominal lamp rating:			
230 V incandescent/halogen	W	800	2000
fluorescent tubes with electronic ballast	W	300	800
fluorescent tubes with electromagnetic ballast	W	200	500
CFL	W	100	200
230 V LED	W	100	200
LV halogen or LED with electronic ballast	W	100	200
LV halogen or LED with electromagnetic ballast	W	300	800
Breaking capacity DC1: 24/110/220 V	A	25/5/1	25/5/1
Minimum switching load	mW (V/mA)	1000 (10/10)	1000 (10/10)
Contact material		AgNi	$AgSnO_2$
Coil specification			
Nominal voltage (U_N)	V DC/AC (50/60 Hz)	12 - 24 - 48 - 60 - 120 - 230	12 - 24 - 48 - 60 - 120 - 230
Rated power AC/DC	VA (50 Hz)/W	2/2.2	2/2.2
Operating range	DC/AC (50/60 Hz)	(0.8…1.1)U_N	(0.8…1.1)U_N
Holding voltage	DC/AC (50/60 Hz)	0.4 U_N	0.4 U_N
Must drop-out voltage	DC/AC (50/60 Hz)	0.1 U_N	0.1 U_N
Technical data			
Mechanical life AC/DC	cycles	$2 \cdot 10^6$	$2 \cdot 10^6$
Electrical life at rated load AC-7a	cycles	$70 \cdot 10^3$	$30 \cdot 10^3$
Operate/release time	ms	30/20	30/20
Insulation between coil and contacts (1.2/50 µs)	kV	6	6
Ambient temperature range	°C	–25…+50	–25…+50
Protection category		IP 20	IP 20
Approvals (according to type)			

* Contact gap ≥ 3 mm for NO contacts only;
NC contacts ≥ 1.5 mm

L

25 A modular contactor - 4 pole

- 35 mm wide
- NO contact gap ≥ 3 mm, double break
- Continuous duty for the coil and contacts
- AC/DC silent coil (with varistor protection)
- Protective separation (reinforced insulation) between coil and contacts
- Mechanical and LED indicators as standard
- Auto-On-Off selector version available
- AgNi and $AgSnO_2$ contact versions available
- Compliant with EN 61095: 2009
- Auxiliary contact module available, quick-assembly with the main contactor (1 NO + 1 NC and 2 NO versions)
- For railway applications; materials compliant with fire and smoke characteristics (EN 45545-2 + A1: 2016)
- 35 mm rail (EN 60715) mount

22.34
Box clamp



For outline drawings see page 14

22.34.0.xxx.1xx0



- AgNi contacts, specifically intended for resistive and slightly inductive loads as well as for motor loads

22.34.0.xxx.4xx0



- $AgSnO_2$ contacts, specifically intended for lamp loads and for high inrush current loads



4 NO (x3x0) | 3 NO + 1 NC (x7x0) | 2 NO + 2 NC (x6x0)

Contact specification			
Contact configuration		4 NO, 3 mm* (or 3NO + 1NC or 2NO + 2NC)	
Rated current/Maximum peak current	A	25/80	25/120
Rated voltage	V AC	250/440	250/440
Rated load AC1/AC-7a (per pole @ 250 V)	VA	6250	6250
Rated current AC3/AC-7b	A	10	10
Rated load AC15 (per pole @ 230 V)	VA	1800	1800
Three-phase motor rating (400 - 440 V AC)	kW	4	4
Rated current AC-5a (per pole @ 250 V)	A	15	15
Rated current AC-7c	A	—	10
Nominal lamp rating:			
230 V incandescent/halogen	W	800	2000
fluorescent tubes with electronic ballast	W	300	800
fluorescent tubes with electromagnetic ballast	W	200	500
CFL	W	100	200
230 V LED	W	100	200
LV halogen or LED with electronic ballast	W	100	200
LV halogen or LED with electromagnetic ballast	W	300	800
Breaking capacity DC1: 24/110/220 V	A	25/5/1	25/5/1
Minimum switching load	mW (V/mA)	1000 (10/10)	1000 (10/10)
Contact material		AgNi	$AgSnO_2$
Coil specification			
Nominal voltage (U_N)	V DC/AC (50/60 Hz)	12 - 24 - 48 - 60 - 120 - 230	12 - 24 - 48 - 60 - 120 - 230
Rated power AC/DC	VA (50 Hz)/W	2/2.2	2/2.2
Operating range	DC/AC (50/60 Hz)	(0.8…1.1)U_N	(0.8…1.1)U_N
Holding voltage	DC/AC (50/60 Hz)	0.4 U_N	0.4 U_N
Must drop-out voltage	DC/AC (50/60 Hz)	0.1 U_N	0.1 U_N
Technical data			
Mechanical life AC/DC	cycles	$2 \cdot 10^6$	$2 \cdot 10^6$
Electrical life at rated load AC-7a	cycles	$150 \cdot 10^3$	$30 \cdot 10^3$
Operate/release time	ms	18/40	18/40
Insulation between coil and contacts (1.2/50 µs)	kV	6	6
Ambient temperature range	°C	–25…+50	–25…+50
Protection category		IP 20	IP 20
Approvals (according to type)			

* Contact gap ≥ 3 mm for NO contacts only;
NC contacts ≥ 1.5 mm

L

X-2025, www.findernet.com

40 - 63 A modular contactor - 4 pole

- NO and NC contact gap ≥ 3 mm, double break
- Continuous duty for the coil and contacts
- AC/DC silent coil (with varistor protection)
- Protective separation (reinforced insulation) between coil and contacts
- Mechanical indicator as standard
- Compliant with EN 60947-4-1 (Mirror Contact) version available
- Auxiliary modules compliant with EN 60947-5-1 (mechanically linked contacts)
- $AgSnO_2$ contacts
- Compliant with EN 61095: 2009
- 35 mm rail (EN 60715) mount

22.44.0.xxx.4xxx	**22.64.0.xxx.4xxx**
	
• For high inrush current loads 176 A • Contact material $AgSnO_2$	• Specifically intended: for high inrush current loads 240 A • Contact material $AgSnO_2$

22.44/22.64
Box clamp





4 NO (4310)



3 NO + 1 NC (4710)



4 NC (4410)



2 NO + 2 NC (4610)



3 NO + 1 NC (4717)

For outline drawings see page 14

Contact specification			
Contact configuration		4 NO, (or 3 NO + 1 NC or 2 NO + 2 NC or 4 NC) ≥ 3 mm	
Rated current/Maximum peak current	A	40/176	63/240 (NO) - 50/— (4 NC)
Rated voltage/Maximum switching voltage	V AC	400/480	400/480 (NO)
Rated load AC1 / AC-7a (per pole @ 400 V)	VA	26000	40000 (NO) - 32900 (4 NC)
Rated current AC3 / AC-7b (400 V)	A	22	30 (NO)
Three-phase motor rating (400 - 440 V AC)	kW	11	15 (NO)
Rated current AC-5a (per pole @ 250 V)	A	20	32 (NO)
Rated current AC-7c	A	—	—
Nominal lamp rating (NO):			
230 V incandescent/halogen	W	4000	5000
fluorescent tubes with electronic ballast	W	1500	2000
fluorescent tubes with electromagnetic ballast	W	1500	2000
CFL	W	1000	1500
230 V LED	W	1000	1500
LV halogen or LED with electronic ballast	W	1000	1500
LV halogen or LED with electromagnetic ballast	W	1500	2000
Breaking capacity DC1 (NO): 24/110/220 V	A	40/4/1.2	63/4/1.2
Minimum switching load	mW (V/mA)	1000 (17/50)	1000 (17/50)
Contact material		$AgSnO_2$	$AgSnO_2$
Coil specification			
Nominal voltage (U_N)	V DC/AC (50/60 Hz)	12 - 24 - 110…120 (110 V DC) - 230…240 (220 V DC)	
Rated power AC/DC	VA (50 Hz)/W	6	6
Operating range	DC/AC (50/60 Hz)	(0.85…1.1)U_N	(0.85…1.1)U_N
Holding voltage	DC/AC (50/60 Hz)	0.85 U_N	0.85 U_N
Must drop-out voltage	DC/AC (50/60 Hz)	0.2 U_N	0.2 U_N
Technical data			
Mechanical life AC/DC	cycles	$3 \cdot 10^6$	$3 \cdot 10^6$
Electrical life at rated load AC-7a	cycles	$100 \cdot 10^3$	$100 \cdot 10^3$
Operate/release time	ms	20/45	20/45
Insulation between coil and contacts (1.2/50 µs)	kV	6	6
Ambient temperature range	°C	See table Current - Temperature derating (page 9)	
Protection category		IP 20	IP 20
Approvals (according to type)			

32 A modular contactor - 2 or 4 pole

- NO and NC contact gap ≥ 3 mm, double break
- Continuous duty for the coil and contacts
- AC/DC silent coil (with varistor protection)
- Protective separation (reinforced insulation) between coil and contacts
- Mechanical indicators as standard
- Compliant with EN 60947-4-1 (Mirror Contact) version available
- AgNi contacts
- Compliant with EN 61095: 2009
- 35 mm rail (EN 60715) mount

22.72/22.74
Box clamp



For outline drawings see page 14

NEW 22.72.0.xxx.1x1x



- 17.5 mm wide
- Contact material AgNi



NEW 22.74.0.xxx.1x1x



- 35 mm wide
- Contact material AgNi



Contact specification			
Contact configuration		2 NO, 1 NO + 1 NC, 2 NC	4 NO, 3 NO + 1 NC, 2 NO + 2 NC, 4 NC
Rated current/Maximum peak current	A	32/72	32/68
Rated voltage	V AC	230/400	230/400
Rated load AC1 / AC-7a (per pole @ 400 V)	VA	7000/—	7000/21 000
Rated current AC3 / AC-7b (per pole @ 400 V)	A	9 (NO) - 6 (NC)	8.5 (NO) - 8.5 (NC)
Single/Three-phase motor rating	kW	1.3 (NO) - 0.75 (NC) (@230 V AC)	4 (@400 V AC)
Rated current AC-5a (per pole @ 250 V)	A	13	13
Rated current AC-7c	A	—	—
Rated current AC15	A	12	12
Nominal lamp rating:			
230 V incandescent/halogen	W	2500	2500
fluorescent tubes with electronic ballast	W	700	700
CFL	W	250	250
230 V LED	W	300	300
LV halogen or LED with electronic ballast	W	300	300
LV halogen or LED with electromagnetic ballast	W	500	500
Breaking capacity DC1: 24/110/220 V	A	32/6/0.6	32/6/0.6
Minimum switching load	mW (V/mA)	1000 (17/50)	1000 (17/50)
Contact material		AgNi	AgNi
Coil specification			
Nominal voltage (U_N)	V DC/AC (50/60 Hz)	24 - 48 - 110 - 220/24 - 48 - 110 - 230	
Rated Power AC/DC	VA (50 Hz)/W	2.1	2.6/3.8 (4 NC)
Operating range	AC/DC (50/60 Hz)	(0.85…1.1)U_N	
Holding voltage	AC/DC (50/60 Hz)	0.85 U_N	
Must drop-out voltage	AC/DC (50/60 Hz)	0.2 U_N	
Technical data			
Mechanical life AC/DC	cycles	10 000 000	10 000 000
Electrical life at rated load AC-7a	cycles	150 000 (NO)/100 000 (NC)	150 000
B10d - AC1 (230 V - 32 A)		150 000	150 000
Operate/release time	ms	45/50	45/70
Insulation between coil and contacts (1.2/50 µs)	kV	4	4
Ambient temperature range	°C	See table Current - Temperature derating (page 9)	
Protection category		IP 20	IP 20
Approvals (according to type)			

X-2025, www.findernet.com

Ordering information

Exemple: 22 series, modular contactor 25 A, 4 NO contacts, coil 230 V AC/DC, $AgSnO_2$ contacts, Auto-On-Off selector + mechanical indicator + LED, standard version.

								A	B	C	D	
2	2	.	3	4	.	0	.	2	3	0	.	4	3	4	0

Series

Type
3 = 25 A modular contactor range
4 = 40 A modular contactor range
6 = 63 A modular contactor range
7 = 32 A modular contactor range

Number of contacts
2 = 2 pole
4 = 4 pole

Coil version
0 = AC (50/60 Hz)/DC

Coil rated voltage
See coil specifications

D: Special versions
0 = Standard
7 = Conform to EN 60947-4-1: Mirror contacts

C: Options
1 = Mechanical indicator
2 = Mechanical indicator + LED
4 = Auto-On-Off selector + mechanical indicator + LED

B: Contact circuit
3 = All NO contacts
4 = All NC contacts (22.32, 22.64, 22.72 and 22.74)
5 = 1 NO + 1 NC (SPST-NO + SPST-NC)
6 = 2 NO + 2 NC (DPST-NO + DPST-NC)
7 = 3 NO + 1 NC (3PST-NO + SPST-NC)

A: Contact material
1 = AgNi
4 = $AgSnO_2$

Selecting features and options: only combinations in the same row are possible.
Preferred selections for best availability are shown in **bold.**

Type	Coil version	A	B	C	D
22.32	AC/DC	**1 - 4**	**3** - 4 - 5	**2 - 4**	0
22.34	AC/DC	**1 - 4**	**3** - 6 - 7	**2 - 4**	0
22.44	AC/DC	**4**	**3** - 6 - 7	**1**	0 - 7
22.64	AC/DC	**4**	**3** - 4 - 6 - 7	**1**	0 - 7
22.72	AC/DC	**1**	**3** - 4 - 5	**1**	0 - 7
22.74	AC/DC	**1**	**3** - 4 - 6 - 7	**1**	0 - 7

L

Options

22.xx.x.xxx.xx4x – Auto-On-Off selector + mechanical indicator + LED (for Type 22.32 / 22.34)



1. **Selector**
   The three-position manual selector has the following functions:
   - **ON position** - the contacts are latched in the operated state (NO contacts - closed and NC contacts - open), the mechanical indicator is visible in its window, the LED is not illuminated.
   - **AUTO position** - the state of contacts, mechanical indicator and LED follow the coil supply voltage.
   - **OFF position** - even if terminals A1 - A2 are supplied with rated voltage, the coil is not energized, and so the contacts remain in the non-operated state, the mechanical indicator is not visible and the LED is not illuminated.
2. **LED**
3. **Mechanical indicator**

22.xx.x.xxx.xx1x – Mechanical indicator (for Type 22.44 / 22.64 / 22.72 / 22.74)



1. **Mechanical indicator**

L

X-2025, www.findernet.com

Technical data

Insulation		**22.32/22.34**		**22.44/22.64**	**22.72/22.74**
Rated insulation voltage	V AC	250	440	440	440
Pollution degree		3*	2	3	3
Insulation between coil and contact set					
Type of insulation		Reinforced		Reinforced	Reinforced
Overvoltage category		III		III	III
Rated impulse voltage	kV (1.2/50 µs)	6		4	4
Dielectric strength	V AC	4000		2000	2000
Insulation between adjacent contacts					
Type of insulation		Basic		Basic	Basic
Overvoltage category		III		III	III
Rated impulse voltage	kV (1.2/50 µs)	4		4	4
Dielectric strength	V AC	2500		2000	2000
Insulation between open contacts		**NO contact**	**NC contact**	**NO/NC contacts**	**NO/NC contacts**
Contact gap	mm	3	1.5	3	3
Overvoltage category		III	II	III	III
Rated impulse voltage	kV (1.2/50 µs)	4	2.5	4	4
Dielectric strength	V AC/kV (1.2/50 µs)	2500/4	2000/3	2000/3	2000

* Only for versions without Auto-On-Off selector. For versions with Auto-On-Off selector pollution degree 2 applies.

Insulation between coil terminals					
Rated impulse voltage (surge) differential mode (according to EN 61000-4-5)	kV (1.2/50 µs)	4		2	2
Short circuit protection		**22.32 / 22.34**	**22.44**	**22.64**	**22.72/22.74**
Rated conditional short circuit current	kA	3	3	3	3
Back-up fuse	A	32 (gL/gG type)	63	80	32

Terminals		**Solid and stranded cable**		
		22.32 / 22.34	**22.44 / 22.64**	**22.72/22.74**
Max. wire size – contact terminals	mm^2	1 x 6 / 2 x 4	1 x 25 (solid) - 1 x 16 (stranded)	1 x 10 (solid) 1 x 6 (stranded)
	AWG	1 x 10 / 2 x 12	1 x 4 (solid) - 1 x 6 (stranded)	1 x 7 (solid) 1 x 9 (stranded)
Max. wire size – coil terminals	mm^2	1 x 4 / 2 x 2.5	1 x 2.5	1 x 2.5
	AWG	1 x 12 / 2 x 14	1 x 14	1 x 14
Min. wire size – contact and coil terminals	mm^2	1 x 0.2	1 x 1 (coil) - 1 x 1.5 (contacts)	1 x 1 (coil) - 1 x 1 (contacts)
	AWG	1 x 24	1 x 18 (coil) - 1 x 16 (contacts)	1 x 17 (coil) - 1 x 1 (contacts)
Screw torque	Nm	0.8	1.2 (coil terminals) - 3.5 (contact terminals)	0.6 (coil terminals) - 1.2 (contact terminal)
Wire strip length	mm	9	10	7 (coil) - 9 (terminals)

Other data			**22.32**	**22.34**	**22.44**	**22.64**	**22.72/22.74**
Vibration resistance (10…150)Hz		g	4	4	3	3	3
Shock resistance		g	10	10	15	15	15
Power lost to the environment	without contact current	W	2	2	6	6	2.8
	with rated current	W	4.8	6.3	17	37	12.8

Note

22.32/22.34: It is suggested an air gap of 9 mm between adjacent relays for installations and working conditions close to the limit (that is, ambient temperature > 40 °C, coil operated for a prolonged period of time, all contacts loaded with current > 20 A).

22.44/22.64: The maximum ambient temperature with 3 adjacent contactors is + 40 °C; when more than 3 contactors are installed, it is necessary an air gap of 9 mm. With 2 adjacent contactors the maximum ambient temperature is + 55 °C; when more than 2 contactors are installed, it is necessary an air gap of 9 mm.

Current - Temperature derating

Type of contactor			**22.72**	**22.74**	**22.44**	**22.64**
Rated current		A	32	32	40	63
Operating ambient temperature			–25 °C…+55°C(In)…+70 °C (2NO contacts)	–25 °C…+55°C(In)…+70 °C (4 NO contacts)		
			–15 °C…+55 °C (1NO+1NC contacts)	–15 °C…+55°C(In)…+70 °C (3 NO + 1 NC contacts)		
			–15 °C…+55 °C (2NC contacts)	–15 °C…+55 °C (2 NO + 2 NC contacts)		
			—	–15 °C…+55 °C (4 NC contacts)		
Max. thermal current up to +55 °C		A	32	32	40	63 (NO) - 50 (4 NC)
Max. thermal current @ +70 °C		A	25	25	40	50 (NO)
Number of contactors side-by-side:	≤40 °C		max. 3			
	(40…55) °C		max. 2			
	(55…70) °C		max. 1 (ventilation madule or least 9 mm free space on each side)			
Min. conductor @ thermal current @ +70 °C		mm^2	6	6	10	16
Tigtening torque - main circuit		Nm	1.2	1.2	3.5	3.5

Contact specification

Ratings and utilization categories according to EN 61095: 2009

Type	Utilization category					
	AC-7a		AC-7b		AC-7c	
	Rated current (A)	Rated electrical life (Cycles)	Rated current (A)	Rated electrical life (Cycles)	Rated current (A)	Rated electrical life (Cycles)
22.32…1xx0 (AgNi contacts)	25	$70 \cdot 10^3$ (NO) $30 \cdot 10^3$ (NC)	10	$30 \cdot 10^3$	—	—
22.32…4xx0 ($AgSnO_2$ contacts)	25	$30 \cdot 10^3$	10	$30 \cdot 10^3$	10	$30 \cdot 10^3$
22.34…1xx0 (AgNi contacts)	25	$150 \cdot 10^3$ (NO) $100 \cdot 10^3$ (NC)	10	$30 \cdot 10^3$	—	—
22.34…4xx0 ($AgSnO_2$ contacts)	25	$30 \cdot 10^3$	10	$30 \cdot 10^3$	10	$30 \cdot 10^3$
22.44…4xx0	40	$100 \cdot 10^3$	22	$150 \cdot 10^3$	—	—
22.64…4xx0	63	$100 \cdot 10^3$	30	$150 \cdot 10^3$	—	—
22.72…1410	32	$150 \cdot 10^3$ (NO) - $100 \cdot 10^3$ (NC)	9 (NO) / 6 (NC)	$30 \cdot 10^4$	—	—
22.74…1410	32	$150 \cdot 10^3$	8.5	$50 \cdot 10^4$	—	—

Utilization category: **AC-7a** = Slightly inductive loads ($\cos\varphi = 0.8$)
AC-7b = Motor loads; ($\cos\varphi = 0.45$, $I_{making} = 6x\ I_{breaking}$)
AC-7c = Compensated electric discharge lamps ($\cos\varphi = 0.9$, C = 10 mF/A)

H 22 - Maximum DC1 breaking capacity - Type 22.32/22.34



H 22 - Maximum DC1 breaking capacity - Type 22.44/22.64



- When switching a resistive load (DC1) having voltage and current values under the curve, an electrical life of ≥ $100 \cdot 10^3$ can be expected.
- In the case of DC13 loads, the connection of a diode in parallel with the load will permit a similar electrical life as for a DC1 load.
  Note: the release time for the load will be increased.

H 22 - Maximum DC1 breaking capacity - Type 22.72/22.74



L

X-2025, www.findernet.com

Coil specifications

AC/DC version data (type 22.32)

Nominal voltage U_N	Coil code	Operating range U_{min}	Operating range U_{max}	Rated coil consumption I_N at U_N (AC)
V		V	V	mA
12	**0**.012	9.6	13.2	165
24	**0**.024	19.2	26.4	83
48	**0**.048	38.4	52.8	42
60	**0**.060	48	66	33
120 (110…125)	**0**.120	88	138	16.5
230 (230…240 AC) (220 DC)	**0**.230	184 (AC) 176 (DC)	264 (AC) 242 (DC)	8.7

AC/DC version data (type 22.34)

Nominal voltage U_N	Coil code	Operating range U_{min}	Operating range U_{max}	Rated coil consumption I_N at U_N (AC)
V		V	V	mA
12	**0**.012	9.6	13.2	165
24	**0**.024	19.2	26.4	83
48	**0**.048	38.4	52.8	42
60	**0**.060	48	66	33
120 (110…125)	**0**.120	88	138	16.5
230 (230…240 AC) (220 DC)	**0**.230	184 (AC) 176 (DC)	264 (AC) 242 (DC)	8.7

AC/DC version data (type 22.44 / 22.64)

Nominal voltage U_N	Coil code	Operating range U_{min}	Operating range U_{max}	Rated coil consumption I_N at U_N (AC)
V		V	V	mA
12	**0**.012	10.2	13.2	495
24	**0**.024	20.4	26.4	250
120 (110…125)	**0**.120	102	138	50
230 (230…240 AC) (220 DC)	**0**.230	196	264 (AC) 242 (DC)	26

AC/DC version data (type 22.72)

Nominal voltage U_N	Coil code	Operating range U_{min}	Operating range U_{max}	Rated coil consumption I_N at U_N (AC)
V		V	V	mA
24	**0**.024	20.4	26.4	98
48	**0**.048	40.8	52.8	44
110	**0**.110	93.5	121	20
230	**0**.230	195.5	253	9.2

AC/DC version data (type 22.74)

Nominal voltage U_N	Coil code	Operating range U_{min}	Operating range U_{max}	Rated coil consumption I_N at U_N (AC)
V		V	V	mA
24	**0**.024	20.4	26.4	110
48	**0**.048	40.8	52.8	54.6
110	**0**.110	93.5	121	24.5
230	**0**.230	195.5	253	10.8

R 22 - Coil operating range v ambient temperature



1 - Max. permitted coil voltage.
2 - Min. pick-up voltage with coil at ambient temperature.

L

Wiring diagrams

Type 22.32



Type 22.34

Line and neutral switched



Type 22.34

Line only switched



Type 22.44/22.64

Line and neutral switched



Type 22.44/22.64

Line only switched



Type 22.xx.4717

Mirror Contacts



Example of application of contactor with Mirror Contacts: Normally closed contact is definitely in open position if the normally open contact is closed

L

X-2025, www.findernet.com

Wiring diagrams

Type 22.72

Phase interruption only



Type 22.74

Phase and neutral interruption



Outline drawings

Type 22.32
Box clamp





Type 22.32 + 022.33/022.35
Box clamp





Type 22.34
Box clamp





Type 22.34 + 022.33/022.35
Box clamp





Types 22.44/22.64
Box clamp





Types 22.44/22.64 + 022.63/022.65
Box clamp





Type 22.72
Box clamp





Types 22.74
Box clamp





L

X-2025, www.findernet.com

Outline drawings

Types 022.33/022.35
Box clamp





Types 022.63/022.65
Box clamp





Types 022.73/022.75
Box clamp





L

Auxiliary modules

Mechanically linked contacts according to Annex L of EN 60947-5-1

		022.33	022.35	022.63	022.65	022.7x	
							
						022.73 	022.75 
Type of contactor		Type 22.32 Type 22.34		Type 22.44 Type 22.64		Type 22.74	
Contact specification							
Contact configuration		2 NO	1 NO + 1 NC	2 NO	1 NO + 1 NC	2 NO	1 NO + 1 NC
Conventional free air thermal current I_{th}	A	6		6		6	
Rated power AC15 (230 V)	VA	700		700		700	
Electrical life at rated load	cycles	$30 \cdot 10^3$		$30 \cdot 10^3$		$30 \cdot 10^3$	
Minimum switching load	mW (V/mA)	1000 (10/10)		1000 (10/10)		1000 (10/10)	
Contact material		AgNi		AgNi		AgNi	
Short circuit protection							
Rated conditional short circuit current	kA	1		1		1	
Back-up fuse	A	6 (gL/gG type)		6 (gL/gG type)		6 (gL/gG type)	
Terminals		**Solid and stranded cable**		**Solid and stranded cable**		**Solid and stranded cable**	
Max. wire size	mm^2	1 x 4 / 2 x 2.5		1 x 2.5		1 x 2.5	
	AWG	1 x 12 / 2 x 14		1 x 14		1 x 14	
Min. wire size	mm^2	1 x 0.2		1 x 1		1 x 1	
	AWG	1 x 24		1 x 18		1 x 18	
Screw torque	Nm	0.6		0.6		0.6	
Wire strip length	mm	9		9		9	
Power lost to the environment							
without contact current	W	—		—		—	
with rated current	W	0.5		0.5		0.5	
Approvals (according to type)		CE UKCA EAC RINA cULus		CE UKCA EAC cULus		CE UKCA	

NOTE: It is not possible to assembly the auxiliary module on 22.32.0.xxx.x4x0 (2 NC versions).



22.32 + 022.33/022.35



22.44 + 022.63/022.65



22.34 + 022.33/022.35



22.64 + 022.63/022.65

X-2025, www.findernet.com

Accessories



020.01

Adaptor for panel mounting (for 22.32 type), plastic, 17.5 mm wide	020.01





011.01

Adaptor for panel mounting (for 22.34 type), plastic, 35 mm wide	011.01





060.48

Sheet of marker tags (CEMBRE Thermal transfer printers) for all relays (48 tags), 6 x 12 mm	060.48



019.01

Identification tag, plastic, 1 tag, 17 x 25.5 mm	019.01



022.09

Separator for rail mounting, plastic, 9 mm wide	022.09





022.18

8-way jumper link for type 22.32, 17.5 mm wide	022.18 (blue)
Rated values	10 A - 250 V





022.26

6-way jumper link for type 22.34, 35 mm wide	022.26 (blue)
Rated values	10 A - 250 V



L