Data Sheet | Item Number: 2587-2147

Switched-mode power supply; Base; 1-phase; 24 VDC output voltage; 20 A output current; DC-OK LED

https://www.wago.com/2587-2147











Similar to illustration

Features:

- Optical status indication
- Suitable for both parallel and series operation
- Natural convection cooling when horizontally mounted
- Connection technology with push-in termination
- Electrically isolated output voltage (SELV) per EN 62368-1/UL 61010-1

Technical data

Input

Phases	1
Nominal input voltage $U_{i\,nom}$	1 x 100 … 240 VAC
Input voltage range	1 x 90 … 264 VAC (Derating -1 %/V for voltage < 100 VAC)
Nominal mains frequency range	50 Hz / 60 Hz
Input current I_i	≤ 7 A
Inrush current	≤ 20 A (at 230 VAC / 25 °C)
Power factor	≥ 0.98 (230 VAC)
Power factor correction (PFC)	Active
Mains failure hold-up time	≥ 16 ms (230 VAC)

Output

Nominal output voltage $U_{o\,nom}$	24 VDC (SELV)
Output voltage range	23.5 … 28 VDC (adjustable)
Default Setting	DC 24 V
Nominal output current $I_{o\,nom}$	20 A
Nominal output power	480 W
Deviation	≤ 1 %
Residual ripple	≤ 100 mV (peak-to-peak)
Overload behavior	Shutdown and automatic restart in the event of a short circuit

Signaling and communication

Signaling	Optical status indication (DC OK)

Efficiency/power losses

Power loss P_l	≤ 5 W (no load); ≤ 32.5 W (Full load)
Efficiency (typ.)	94 %

Circuit protection

Internal fuse	T 8 A / 250 V

Safety and protection

Isolation voltage (pri.-sec., AC)	3510 V
Isolation voltage (pri.-PE, AC)	2210 V
Protection class	I
Protection type	IP20; per EN 60529
Overvoltage category	III (≤ 2000 m); II (> 2000 m)
Pollution degree	2
Short-circuit-protected	Yes
Open-circuit-proof	Yes
Parallel operation	Yes
Series operation	Yes
MTBF	> 1,000,000 h (at 25 °C; per IEC 61709; SN 29500)

Connection data

Connection 1

Connection type 1	Input/output
Connection technology	Push-in CAGE CLAMP®
WAGO connector	WAGO Serie 2626
Solid conductor	0.2 … 10 mm² / 24 … 8 AWG
Fine-stranded conductor	0.2 … 10 mm² / 24 … 8 AWG
Fine-stranded conductor; with insulated ferrule	0.25 … 6 mm²
Fine-stranded conductor; with uninsulated ferrule	0.25 … 6 mm²
Strip length	13 … 15 mm / 0.51 … 0.59 inches

Continued on next page

Physical data

Width	56 mm / 2.2 inches
Height	125 mm / 4.92 inches
Depth from upper-edge of DIN-rail	138 mm / 5.43 inches

Mechanical data

Mounting type	DIN-35 rail

Material data

Fire load	0 MJ
Weight	1149 g

Environmental requirements

Ambient temperature (operation)	-30 … +70 °C (device starts at -40 °C (type-tested))
Ambient temperature (storage)	-40 … +85 °C
Relative humidity	5 … 96 % (no condensation permissible)
Derating	-9.6 W/°C (> 45 °C and < 200 V); -9.6 W/°C (> 50 °C and ≥ 200 V)
Climatic category	3K3 (per EN 60721)
Operating altitude (max.)	5000 m

Standards and specifications

Conformity marking	CE
Standards/specifications	EN 62368-1 EN 55032 EN 55035 EN IEC 61000-3-2 EN 61000-3-3 EN IEC 61000-6-4 EN IEC 61000-6-2 UL 61010-1 UL 61010-2-201

Commercial data

PU (SPU)	1 pcs
Packaging type	Box
Country of origin	CN
GTIN	4066966626698
Customs tariff number	85044083900

Product classification

UNSPSC	39121004

Environmental Product Compliance

RoHS Compliance Status	Compliant,No Exemption

Approvals / Certificates

General approvals

Approval	Standard	Certificate Name
UL Underwriters Laboratories Inc.	UL 61010-2-201	E255817

Declarations of conformity and manufacturer's declarations

Approval	Standard	Certificate Name
EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-
UK-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2587-2147

Documentation

Bid Text

2587-2147	14.04.2025	docx 45.37 KB	
2587-2147	14.04.2025	x81 7.24 KB	

Instruction Leaflet

Power Supply BASE	V 3.0.0 10.09.2024	pdf 653.79 KB	

CAD/CAE-Data

CAD data

2D/3D Models 2587-2147