ALUMINUM ELECTROLYTIC CAPACITORS · SNAP-IN TYPE

CD **29L** QL SERIES

7 000h at 85°C

- Larger Size Components
- Long Useful Life
- High Ripple Current
- Industrial Power Supplies



ITEM — CHARACTERISTICS

Operating Temperature Range (°C)	-40 ~ +85	-25 ~ +85	
Voltage Range (V)	160 ~ 400	450 ~ 500	Lower Voltages on request.
Capacitance Range (µF)	390 ~ 4 700		
Capacitance Tolerance (20°C, 120Hz)	± 20%		

The usage at lower temperatures than indicated may be possible. Please contact the Jianghai Europe sales office for approval.

Leakage Current	After 5 minutes at 20°C application of rated voltage, leakage current is not more than specified in table.

Stability at Low Temperature (Impedance Ratio at 120Hz)	Rated Voltage (V)	160 ~ 200	250 ~ 400	450	500
	$Z_{-25°C} / Z_{+20°C}$	3	4		
	$Z_{-40°C} / Z_{+20°C}$	6	8	-	

Fast Charge-Discharge: **Please contact Jianghai for an appropriate choice of the capacitor or possible technical adaptions, esp. for applications like: Welding, Photoflash, Servo motors, X-Ray**

ITEM	USEFUL LIFE		LOAD LIFE	ENDURANCE TEST	SHELF LIFE	
Lifetime	7 000h	> 100 000h	5 000h	5 000h	1 000h	
Leakage Current	Not more than specified value		Not more than specified value	Not more than specified value	Not more than specified value	
Capacitance Change	Within ± 30% of initial value		Within ± 20% of initial value	Within ± 20% of initial value	Within ± 20% of initial value	
Dissipation Factor	Not more than 300% of specified value		Not more than 200% of specified value	Not more than 200% of specified value	Not more than 200% of specified value	
Condition: Applied Voltage Applied Current Applied Temperature	U_R I_R 85°C	U_R 1,2 x I_R 40°C	U_R I_R 85°C	U_R I_R = 0 85°C IEC 60384	U_R = 0 I_R = 0 85°C	After test: U_R to be applied for 30 min > 24h before measurement

MULTIPLIER FOR RIPPLE CURRENT (FREQUENCY COEFFICIENT)

Rated Voltage (V) \ Frequency	50Hz	120Hz	300Hz	1kHz	10kHz	≥50kHz
≥ 160	0,80	1,00	1,16	1,30	1,41	1,45

Multipliers for typical operating conditions.

Max. Current Snap-In Terminal: 15A. For more current use Lug-Terminals.

MULTIPLIER FOR LIFETIME (LIFETIME DIAGRAM) $U_R \geq 160V$



I_A = actual ripple current at 120Hz,
I_R = rated ripple current at 120Hz, 85°C
Multiplier of Useful Life as a function of ambient temperature & ripple current load

ENVIRONMENTAL

The products are RoHS, WEEE and REACh compliant. The detailed version please see seperate "Environmental Certificates" document or www.jianghai-europe.com

SAFETY FACTOR

This diagram includes a safety margin. In many cases the allowed current capability/ lifetime may be increased. For details and approvals please contact the Jianghai Europe sales office.

U_{RDC} (Surge Voltage) Code (V)	C_R Rated Capacitance (µF)	ESR_{max} Equivalent Series Resistance 20°C 120Hz (mΩ)	ESR_{typ} Equivalent Series Resistance 20°C 120Hz (mΩ)	tanδ Dissipation Factor 20°C 120Hz	I_{leak} Leakage Current (mA)	I_{RAC} Rated Ripple Current 85°C 120Hz (Arms)	Size øD x L (mm)	ORDER CODE ◊◊ = pin style & length ΔΔ = pin number Details: Page 4
160 (200) 2C	2 200	91	63	0,15	1,5	4,9	35 x 45	ECS2CQL222M◊◊ΔΔ3545
	2 700	74	52	0,15	1,5	5,3	35 x 50	ECS2CQL272M◊◊ΔΔ3550
	3 300	61	42	0,15	1,5	5,5	35 x 70	ECS2CQL332M◊◊ΔΔ3570
		61	42	0,15	1,5	5,5	40 x 60	ECS2CQL332M◊◊ΔΔ4060
	3 900	52	36	0,15	1,5	5,9	35 x 80	ECS2CQL392M◊◊ΔΔ3580
	4 700	43	30	0,15	1,5	7,3	40 x 80	ECS2CQL472M◊◊ΔΔ4080
200 (250) 2D	1 500	133	93	0,15	1,5	4,3	35 x 40	ECS2DQL152M◊◊ΔΔ3540
	1 800	111	77	0,15	1,5	4,7	35 x 45	ECS2DQL182M◊◊ΔΔ3545
	2 200	91	63	0,15	1,5	5,4	35 x 50	ECS2DQL222M◊◊ΔΔ3550
		91	63	0,15	1,5	5,4	40 x 40	ECS2DQL222M◊◊ΔΔ4040
	2 700	74	52	0,15	1,5	5,9	35 x 60	ECS2DQL272M◊◊ΔΔ3560
		74	52	0,15	1,5	5,9	40 x 50	ECS2DQL272M◊◊ΔΔ4050
	3 300	61	42	0,15	1,5	6,5	35 x 80	ECS2DQL332M◊◊ΔΔ3580
		61	42	0,15	1,5	6,5	40 x 60	ECS2DQL332M◊◊ΔΔ4060
	3 900	52	36	0,15	1,5	7,0	40 x 80	ECS2DQL392M◊◊ΔΔ4080
	4 700	43	30	0,15	1,5	9,2	40 x 90	ECS2DQL472M◊◊ΔΔ4090
250 (300) 2E	1 000	199	139	0,15	1,5	3,5	35 x 35	ECS2EQL102M◊◊ΔΔ3535
	1 200	166	116	0,15	1,5	3,6	35 x 40	ECS2EQL122M◊◊ΔΔ3540
	1 500	133	93	0,15	1,5	4,2	35 x 45	ECS2EQL152M◊◊ΔΔ3545
	1 800	111	77	0,15	1,5	4,6	35 x 50	ECS2EQL182M◊◊ΔΔ3550
		111	77	0,15	1,5	4,6	40 x 40	ECS2EQL182M◊◊ΔΔ4040
	2 200	91	63	0,15	1,5	5,1	35 x 60	ECS2EQL222M◊◊ΔΔ3560
	2 700	74	52	0,15	1,5	6,0	40 x 60	ECS2EQL272M◊◊ΔΔ4060
400 (450) 2G	560	356	249	0,15	1,5	3,0	35 x 45	ECS2GQL561M◊◊ΔΔ3545
		356	249	0,15	1,5	2,8	40 x 40	ECS2GQL561M◊◊ΔΔ4040
	680	293	205	0,15	1,5	3,5	35 x 50	ECS2GQL681M◊◊ΔΔ3550
		293	205	0,15	1,5	3,3	40 x 40	ECS2GQL681M◊◊ΔΔ4040
	820	243	170	0,15	1,5	3,8	35 x 50	ECS2GQL821M◊◊ΔΔ3550
		243	170	0,15	1,5	4,1	40 x 50	ECS2GQL821M◊◊ΔΔ4050
	1 000	199	139	0,15	1,5	4,4	35 x 55	ECS2GQL102M◊◊ΔΔ3555
		199	139	0,15	1,5	4,8	40 x 60	ECS2GQL102M◊◊ΔΔ4060
	1 200	166	116	0,15	1,5	5,3	35 x 70	ECS2GQL122M◊◊ΔΔ3570
		166	116	0,15	1,5	5,5	40 x 60	ECS2GQL122M◊◊ΔΔ4060
	1 500	133	93	0,15	1,5	6,5	40 x 80	ECS2GQL152M◊◊ΔΔ4080
		133	93	0,15	1,5	6,3	45 x 60	ECS2GQL152M◊◊ΔΔ4560
	1 800	111	77	0,15	1,5	7,3	35 x 90	ECS2GQL182M◊◊ΔΔ3590
		111	77	0,15	1,5	7,9	40 x 100	ECS2GQL182M◊◊ΔΔ40100
	2 200	91	63	0,15	1,5	8,6	40 x 100	ECS2GQL222M◊◊ΔΔ40100
		91	63	0,15	1,5	8,1	45 x 80	ECS2GQL222M◊◊ΔΔ4580
450 (500) 2W	470	424	296	0,15	1,5	2,7	35 x 45	ECS2WQL471M◊◊ΔΔ3545
	560	356	249	0,15	1,5	3,1	35 x 50	ECS2WQL561M◊◊ΔΔ3550
		293	205	0,15	1,5	3,1	40 x 40	ECS2WQL561M◊◊ΔΔ4040
	680	293	205	0,15	1,5	3,5	35 x 60	ECS2WQL681M◊◊ΔΔ3560
		293	205	0,15	1,5	3,4	40 x 50	ECS2WQL681M◊◊ΔΔ4050
	820	243	170	0,15	1,5	4,4	35 x 70	ECS2WQL821M◊◊ΔΔ3570
		243	170	0,15	1,5	4,4	40 x 60	ECS2WQL821M◊◊ΔΔ4060
	1 000	199	139	0,15	1,5	5,2	35 x 80	ECS2WQL102M◊◊ΔΔ3580
		199	139	0,15	1,5	5,2	40 x 60	ECS2WQL102M◊◊ΔΔ4060
	1 200	166	116	0,15	1,5	5,9	40 x 70	ECS2WQL122M◊◊ΔΔ4070
		166	116	0,15	1,5	6,0	45 x 60	ECS2WQL122M◊◊ΔΔ4560
	1 500	133	93	0,15	1,5	6,8	40 x 85	ECS2WQL152M◊◊ΔΔ4085
		133	93	0,15	1,5	6,7	45 x 70	ECS2WQL152M◊◊ΔΔ4570
	1 800	111	77	0,15	1,5	7,6	40 x 100	ECS2WQL182M◊◊ΔΔ40100
	2 200	91	64	0,15	1,5	8,6	45 x 100	ECS2WQL222M◊◊ΔΔ45100

U_{RDC} (Surge Voltage) Code (V)	C_R Rated Capacitance (µF)	ESR_{max} Equivalent Series Resistance 20°C 120Hz (mΩ)	ESR_{typ} Equivalent Series Resistance 20°C 120Hz (mΩ)	tanδ Dissipation Factor 20°C 120Hz	I_{leak} Leakage Current (mA)	I_{RAC} Rated Ripple Current 85°C 120Hz (Arms)	Size øD x L (mm)	ORDER CODE ◊◊ = pin style & length ΔΔ = pin number Details: Page 4
500 (550) 2H	390	511	357	0,15	1,5	2,4	35 x 45	ECS2HQL391M◊◊ΔΔ3545
	470	424	296	0,15	1,5	2,8	35 x 50	ECS2HQL471M◊◊ΔΔ3550
	560	356	249	0,15	1,5	3,3	35 x 60	ECS2HQL561M◊◊ΔΔ3560
		356	249	0,15	1,5	3,3	40 x 50	ECS2HQL561M◊◊ΔΔ4050
	680	293	205	0,15	1,5	3,8	35 x 70	ECS2HQL681M◊◊ΔΔ3570
		293	205	0,15	1,5	3,7	40 x 60	ECS2HQL681M◊◊ΔΔ4060
	820	243	170	0,15	1,5	4,6	35 x 80	ECS2HQL821M◊◊ΔΔ3580
		243	170	0,15	1,5	4,6	40 x 70	ECS2HQL821M◊◊ΔΔ4070
	1 000	199	139	0,15	1,5	5,4	40 x 80	ECS2HQL102M◊◊ΔΔ4080
		199	139	0,15	1,5	5,4	45 x 70	ECS2HQL102M◊◊ΔΔ4570
	1 200	166	116	0,15	1,5	6,4	40 x 90	ECS2HQL122M◊◊ΔΔ4090
	1 500	133	93	0,15	1,5	7,2	40 x 100	ECS2HQL152M◊◊ΔΔ40100

ORDER CODE SNAP-IN TYPE

EC	S	2G	QC	221	M	T6	P2	2535	-	JExxxxx
Techno-logy	Terminal Type	Rated Voltage Code	Series Code	Capacitance Code	Capacitance Tolerance	Terminal Style	Terminal / Pitch	Dimension (mm)	Material Code	for Specials only

Techno-logy	Terminal Type		Rated Voltage Code		Series Code		Capacitance Code		Capacitance Tolerance		Terminal Style		Terminal / Pitch		Dimension (mm)		Material Code	
EC = Electrolytric Capacitor	Snap-In	**S**	6,3V	**0J**	CD 293	**BZ**	0,1	**0R1**	**±20%**	**M**	4,0mm Pin Length	**T/L4**	**2 Pin**	**P2**	22x40	**2240**	Standard	**-**
			10V	**1A**	CD 294	**BW**	0,47	**R47**	±10%	**K**	**6,3mm Pin Length**	**T/L6**	3 Pin	**P3**	30x45	**3045**	PVC	**V**
			16V	**1C**	CD 295	**BC**	1,0	**010**	+30/-10%	**Q**	Soldering Pin	**S4**	4 Pin	**P4**	35x80	**3580**	PET	**E**
			20V	**1D**	CD 295S	**BS**	2,2	**2R2**	+20/-0%	**R**	on request: alternative pin types		5 Pin	**P5**	45x100	**45100**		
			25V	**1E**	CD 296	**KC**	100	**101**	±15%	**L**			6 Pin	**P6**	50x105	**50105**		
			35V	**1V**	CD 296L	**FL**	1 000	**102**	+20/-10%	**V**	**= preferred**							
			40V	**1G**	CD 297	**BB**	10 000	**103**										
			50V	**1H**	CD 299	**PG**												
			63V	**1J**	CD 29C	**QC**												
			80V	**1K**	CD 29CS	**DS**												
			100V	**2A**	CD 29H	**QH**												
			125V	**2B**	CD 29HD	**QF**												
			160V	**2C**	CD 29L	**QL**												
			180V	**2K**	CD 29U	**CU**												
			200V	**2D**	CD 29UH	**UT**												
			250V	**2E**	CD 840	**ZQ**												
			315V	**2F**	CD 891	**ZJ**												
			350V	**2V**	CD 892	**ZL**												
			385V	**2J**	CD 895	**ZK**												
			400V	**2G**														
			415V	**2P**														
			420V	**2X**														
			450V	**2W**														
			500V	**2H**														
			550V	**2Y**														
			575V	**2Z**														
			600V	**2S**														
			630V	**J2**														

2 PIN TYPE: T6P2 / T4P2 STANDARD







MOUNTING HOLES



TERMINAL DIMENSIONS

Standard Version: Self-Lock Terminal. Other terminal types and styles on request.
For diameter øD ⩾ 45mm the safety vent is typically placed at the side of the housing.

Terminal	T6 (preferred)	T4
Pin Length T	6,3 mm	4,0 mm
Pin Detail l	3,5 mm	2,5 mm

Max. Current Snap-In Terminal: 15A
For more current please ask for Lug-Terminals.

in mm

3 PIN TYPE: T4P3







MOUNTING HOLES



TERMINAL DIMENSIONS

For diameter øD ⩾ 45mm the safety vent is typically placed at the side of the housing.

Terminal	T6	T4
Pin Length T	-	4,0 mm
Pin Detail l	-	2,5 mm

Max. Current Snap-In Terminal: 15A
For more current please ask for Lug-Terminals.

in mm

4 PIN TYPE: T6P4/T4P4 STANDARD







MOUNTING HOLES



TERMINAL DIMENSIONS

Standard Version: Non-Lock-Terminal. Other terminal types and styles on request.
For øD ⩾ 30mm only.
For diameter øD ⩾ 45mm the safety vent is typically placed at the side of the housing.

Terminal	T6 (preferred)	T4
Pin Length T	6,3 mm	4,0 mm
Pin Detail l	3,5 mm	2,5 mm

Max. Current Snap-In Terminal: 15A
For more current please ask for Lug-Terminals.

in mm

4 PIN TYPE: L6P4/L4P4 SELF-LOCK TERMINAL



For øD ⩾ 30mm only. Other terminal types and styles on request.
For diameter øD ⩾ 45mm the safety vent is typically placed at the side of the housing.

Terminal	T6 (preferred)	T4
Pin Length T	6,3 mm	4,0 mm
Pin Detail l	3,5 mm	2,5 mm

Max. Current Snap-In Terminal: 15A
For more current please ask for Lug-Terminals.

in mm

5 PIN TYPE: S4P5 SOLDERING PIN



For øD ⩾ 30mm only.
For diameter øD ⩾ 45mm the safety vent is typically placed at the side of the housing.

Max. Current Snap-In Terminal: 15A
For more current please ask for Lug-Terminals.

in mm

EXAMPLE: AXIAL MOUNTING



For øD ⩾ 25mm only.
Available also for high vibration usage.

Max. Current Snap-In Terminal: 15A
For more current please ask for Lug-Terminals.

in mm

Other Terminal Styles on request.

WARNING

JIANGHAI is not liable for any extent of possible injuries or damages to persons or things, of any kind, caused by the improper application of and/or operating conditions harmful to electrolytic capacitors. Misapplications which may cause failures include, but are not limited to: ripple current or peak current or voltage above specification, operating voltage above surge voltage specified, temperature exposure outside the specified operating temperature range. Examples of harmful operating conditions comprise, but are not limited to: unusual storage or transport temperatures, excessive and/or rapid changes of ambient temperature or humidity, heavy mechanical shock or vibration, corrosive and abrasive particles in the ambient (cooling) air, conducting dust in the ambient (cooling) air, oil or water vapor or corrosive substances, explosive gas or dust, operation under extremely high or low ambient pressure conditions (below or above sea level), superimposed radio frequency voltages, radioactivity. In case of doubt about the impact of operating conditions on capacitor performance, please contact JIANGHAI.

PERSONAL SAFETY

Electrical or mechanical misapplication of electrolytic capacitors may be hazardous. Personal injury or property damage may result from explosion of a capacitor or from the expulsion of electrolyte due to mechanical disruption or the release of a safety vent of a capacitor. In case of injury or skin or eye exposure to electrolyte, immediately seek professional medical advice. Before using electrolytic capacitors in any application, please read these Handling Precautions, familiarizing thoroughly with the information contained herein. Please check before using any of our electrolytic capacitors if these components fulfill the requirements of your application and that warnings and instructions for use are followed.

WARRANTY

The information contained in this catalogue does not form part of any quotation or contract, is believed to be accurate, reliable and up to date. Quality data are based on the statistical evaluations of a large quantity of parts and do not constitute a guarantee in a legal sense. However, agreement on these specifications does mean that the customer may claim for replacement of individual defective capacitors within the terms of delivery. We will not assume any liability beyond the replacement of defective components. This applies in particular to any consequential damage caused by component failure. Furthermore it must be taken into consideration that the figures stated for lifetime, failure rates and outlier percentages refer to the average production status and are therefore to be understood as mean values (statistic expectations) for a large number of delivery lots of identical capacitors. These figures are based on application experience and data obtained from preceding tests under normal conditions, or – for purpose of accelerated aging – more severe conditions. JIANGHAI reserves the right to change these specifications without prior notice. Any application information given is advisory and does not form part of any specification. The products are not primarily designed for use in life support applications, devices or systems where malfunction of these products can reasonably be expected to result in personal injury. JIANGHAI customers using or selling these products for use in such applications without prior written consent of JIANGHAI do so at their own risk and agree fully to indemnify JIANGHAI for any damage resulting from such improper use or sale. This version of the catalogue supersedes all previous versions. Latest versions of datasheets can be found on our homepage: www.jianghai-europe.com. For more details on precautions and guidelines for aluminum electrolytic capacitors, please refer to CENELEC Technical Report CLC/TR 50454:2008 E, "Guide for the application of aluminum electrolytic capacitors".

POLARITY

Electrolytic capacitors are polar and shall never be used with incorrect polarity, as there is a possible danger of shorting or destruction.

RATED VOLTAGE U_R

The rated voltage is marked on the capacitor and defined in the datasheets as U_R. This voltage should never be exceeded and is the maximum peak voltage including any ripple voltages allowed to avoid a shortening of the lifetime or damage of the capacitor. When a ripple current is applied to the capacitor, the sum of the peak ripple voltage and bias DC voltage shall never exceed the rated voltage. It might be necessary to lower the maximum allowed bias DC voltage, when certain ripple currents are applied to the capacitor.

SURGE VOLTAGE

Maximum voltage, which may be applied to the capacitor for short periods of time: max. 1000 cycles of 30 sec. per 6 min., max. 5 pulses per hour. Capacitance drift +/- 15% max.

REVERSE VOLTAGE

Reverse voltages or voltages < 0V are not allowed.

RECOVERY VOLTAGE

Electric potential between the positive and negative terminal may exist as a result of dielectric absorption. Please take action that this load does not damage other devices or scare workers during the production process (sparks possible). If needed please discharge the capacitor through a 1kΩ resistor.

TEMPERATURE RANGE

Use electrolytic capacitors only within the specified operating temperature range.

OVER-CURRENT

Currents exceeding the rated ripple currents should be avoided.

RIPPLE CURRENT/VOLTAGE

The combined value of DC voltage and peak AC voltage (due to ripple current) shall not exceed the rated voltage and shall never be < 0V. Use of aluminum electrolytic capacitors under ripple current with wide amplitudes is equivalent to rapid charge-discharge operation. Never exceed a ripple voltage of $70V_{peak\text{-}peak}$ without additional approval of Jianghai.

RAPID CHARGING/DISCHARGING

Rapid charging/discharging generates severe heat and gas may be emitted which may lead to explosion. Consult JIANGHAI about specially designed capacitors suitable for such kind of applications. Example: Servo Drive Application

BALANCING RESISTORS

Balancing resistors should be utilized if capacitors are used in serial connection. Please choose low-tolerance resistors to limit voltage drift.

CHARGE-DISCHARGE PROOF

JIANGHAI capacitors are charge-discharge proof, which means that 10^6 switching cycles will cause capacitance reduction of less than 10%.

LIFETIME

There are many different lifetime definitions known without any true standard definition. Take special care when capacitors are compared that the capacitors fulfill the needed requirements. JIANGHAI publishes all conditions to be as transparent as possible. In the case of lifetime tests with additional ripple currents, the bias DC voltage must be reduced, so that the sum of bias DC voltage and the peak of the ripple voltage does not exceed the Rated Voltage U_R.

Load life: Period of time, during which the technical parameters of all capacitors stay within the given limits. JIANGHAI defines this without allowing for outliers.

Shelf Life: Definition of time with acceptable drift of capacitor parameters after storage at upper category temperature without load.

VIBRATION AND MECHANICAL STRESS

Capacitors are sensitive to vibration and mechanical forces applied on the leads. Do not use capacitors, which have been dropped onto a rigid surface.

INSULATION

If any defect of the sleeve is visible, the component should not be used – the same holds for any kind of visible damage. A capacitor should be electrically isolated from the following parts: aluminum case, cathode lead wire, anode lead wire and circuit pattern, and auxiliary terminal of snap-in type. The sleeve is not recognized as an isolator and therefore the standard capacitor should not be used in a place where insulation function is needed. Please contact JIANGHAI if a higher grade of insulation is required.

ENVIRONMENTAL CONDITIONS

Avoid direct contact with water, salt solution, oil, dewing conditions. Halogens generally, especially fumigation treatment with bromides and flame retardant agents containing halogens must be avoided. Avoid exposing to direct sunshine, ozone, ultraviolet rays and x-ray radiation. Air Pressure: Max. 150kPa, min. 8kPa. For usage >2000m altitude above sea level current deratings might be necessary. No heavy air pressure changes are allowed. Do not use or store in an environment containing any hazardous gas (e.g., hydrogen sulphide, sulphurous acid, nitrous acid, chlorine, ammonia, bromine, methyl bromide, other halogens) or acidic or alkaline solutions.

STORAGE

Temperature 5 to 35°C, relative humidity below 75%. Electrolytic capacitors may accumulate charge naturally during storage. In this case discharge through a 1kOhm resistor before use (Recovery voltage). Leakage current may be increased after long storage time. In this case the capacitor should be subjected to the rated voltage treatment through a 1kOhm resistor before use for 1 hour, then it should be discharged through a resistor of about 1 Ohm/Volt. Storage times above 1 year should be avoided or rated voltage treatment may be necessary. In accordance to IEC 60384-4 electrolytic capacitors are subject to a reforming process before acceptance testing. Rated voltage is applied via a series resistance (100Ω: $U_R \leq$ 100VDC, 1kΩ: $U_R >$ 100VDC).

SOLDERING

Soldering conditions (temperature, times) should be within specified conditions, especially for SMT components. Avoid high soldering temperatures as this may reduce lifetime or damage the capacitor. Do never dip the capacitor body into molten solder. Flux should not be adhered to the capacitor's body but only to its terminals. For details and different methods please contact us.

GLUEING, CLEANING AND COATING

Do not use fixing agents or cleaning substances containing halogens. Do not use coating and moulding components that completely seal the capacitor from the environment. Also, never use solvents containing: halogenated hydrocarbons, alkali, petroleum, trichloroethylene/-ethane, xylene, acetones, trichlorotrifluoroethane, tetrachloroethylene, methylenechloride, chloroform, acetates, ketones, esters, chlorides and bromides.

MOUNTING

Other devices, which are mounted near the capacitor, should not touch the capacitor. Additional heat coming from other components near the capacitor may reduce the lifetime of the capacitor. Do never bend or twist the capacitor after soldering to avoid stress on the leads. Capacitors are not protected against mechanical forces on the leads. Forces on the pins might damage the capacitor. No printed circuit board tracks are allowed between the lead pads of the capacitor.

TRANSPORT

Avoid fumigation and spraying insecticides (especially with bromides) in the import or export procedures which can cause corrosion. This applies also to the finished devices.

MAINTENANCE

Periodical inspection should be carried out for the capacitor: visual inspection to check pressure relief open or leakage of electrolyte, electrical characteristics as leakage current, capacitance, and dissipation factor.

ELECTROLYTE AND SEPARATOR PAPER

Electrolyte and separator paper used in aluminum capacitors may be flammable. Also, electrolyte is electrically conductive. Therefore, in case electrolyte gets in contact with PC board it may cause corrosion of circuit pattern or cause short circuit between patterns, and may lead to smoke generation or ignition in worst case.

CAUTION DURING USE OF CAPACITORS

Do not touch the terminals of capacitors. Keep the capacitor free from conductive solution, such as acids, alkali and so on. Ensure that the operating environment of the equipment into which the capacitor has been built is within the specified conditions mentioned in the catalogue or specification sheets.

SAFETY VENT

The safety vent needs some free space to open properly. Allow for free headroom of at least 2mm for diameter ⩽16mm, more than 3mm for diameter 18-35mm, more than 5mm for case diameter 40mm and larger.

EMERGENCY ACTIONS

When the pressure relief vent is open and some gas blows out from the capacitor, please turn the main switch of the equipment off or pull out the plug from the power outlet immediately. During safety vent operation, extremely hot gas (>100°C) may blow out of the capacitors. Do not stand close to the capacitors. In case of eye contact, rinse the open eye(s) with clean water immediately. In case of ingestion, gargle with water immediately, do not swallow. Do not touch electrolyte but wash skin with soap and water in case of skin contact.

DEFINITION OF ELECTRICAL PARAMETERS

Separate documents as application notes, equivalent circuit diagrams and so on are available on request.

PACKAGING

Please refer to the data book for details. Further information is available on request.

DISPOSAL

Scrapped capacitors are classified as scrapped metal. For disposal they are handled as controllable industrial waste because of the nature of the contents (electrolyte). Most of the material is aluminum and cannot be completely burned.

Jianghai Europe Electronic Components GmbH
VERSION 9/2024

To estimate the Lifetime of a non-solid Aluminum Electrolytic Capacitor from Jianghai, the following formulas can be utilized. The Lifetime depends mainly on the ambient temperature, the ripple current and, within certain limits, the operating voltage applied. Other parameters may also affect the Lifetime. Moreover, L_0 can be interpreted in many different ways, which has a fundamental influence on the numerical result. Jianghai offers a high transparency by publishing the different typical definitions of Lifetimes in each datasheet. Lifetime estimations are approximations by nature. Please let JIANGHAI EUROPE confirm any result before using it. The formulas given here do not constitute part of a contract nor of a specification. The formulas do not cover additional aging effects of certain electrolytic systems or other chemical effects. Also the dimensions of the components may have an effect. Forced cooling or other additional cooling-methods have a strong impact on the Lifetime and are not covered by the formulas as defined. For the estimation and interpretation of Lifetime, a close collaboration with JIANGHAI EUROPE is strongly advised.

STRUCTUAL FORMULA

$$L = L_0 \cdot K_T \cdot K_R \cdot K_V$$

WHERE:

- L Total Lifetime
- L_0 Lifetime under Nominal Load at Upper Category Temperature (see catalogue)
- K_T Temperature Factor
- K_R Ripple Current Factor
- K_V Voltage Factor

K_T TEMPERATURE FACTOR

Aluminum Electrolytic Capacitors follow roughly the 10K rule of Arrhenius. It is possible to estimate the Lifetime by rule of thumb: When the operational temperature is reduced by 10K, the Lifetime will double. The formula for $\mathbf{K_T}$ in detail is:

$$K_T = 2^{\frac{T_0 - T_A}{10K}}$$

WHERE:

- T_0 Rated Temperature
- T_A Ambient Temperature

FREQUENCY CORRECTION FACTORS:

If the actual Ripple Currents are not given at the same frequency like I_0, correction factors need to be applied.

$$I_A = \sqrt{\left(\frac{I_{f1}}{F_{f1}}\right)^2 + \left(\frac{I_{f2}}{F_{f2}}\right)^2 + \ldots \left(\frac{I_{fn}}{F_{fn}}\right)^2}$$

K_R RIPPLE CURRENT FACTOR

To estimate the influence of ripple current on lifetime, Jianghai uses a safety factor K_i. Under certain conditions this value can be set to K_i=2, which is prolonging the lifetime. Please contact Jianghai Europe for details and approval.

$$K_R = K_i^{A\frac{\Delta T_0}{10K}}$$

WITH:

$$A = 1 - \left(\frac{I_A}{I_R}\right)^2$$

WHERE:

- I_A Actual Rated Ripple Current
- I_R Ripple Current at Upper Category Temperature (databook value)
- ΔT_0 Core Temperature Rise of the capacitor (typically 3,5 ~ 5K for T_0 = 105°C and 3,5 ~ 10K for T_0= 85°C, see databook value)
- K_i Basis, typically defined as

T_0 = 105°C	$I_A > I_R$:	K_i = 4
	$I_A \leq I_R$:	K_i = 2
T_0 = 85°C		K_i = 2

Remark: Safety Factor K_i may be set as K_i=2 under certain defined conditions. Please contact Jianghai Europe for approval.

>>

K_V VOLTAGE FACTOR

For Radial and SMT Electrolytic Capacitors, this part of the formula has no impact (K_V = 1). But for some bigger capacitors like Snap-In and Screw-Terminal types with rated voltages above 160V, the operating voltage will affect their Lifetime. It is expressed as follows:

FOR:

$$0{,}6 \leq \frac{U_A}{U_R} \leq 1$$

$$K_V = \left(\frac{U_A}{U_R}\right)^{-2{,}5}$$

WHERE:

U_A Actual Operating Voltage

U_R Rated Voltage

FOR:

$$0 < \frac{U_A}{U_R} < 0{,}6$$

$$K_V = 3{,}59$$

FOR:

$$\frac{U_A}{U_R} > 1 \; not\ allowed$$

$$K_V = 1$$

FOR: Radial and SMT Capacitors or $U_R \leqslant 160V$

$$K_V = 1$$

JIANGHAI ELECTROLYTIC CAPACITOR LIFETIME ESTIMATION FORMULA (incl. Safety Factors):

$$L = L_0 \cdot 2^{\frac{T_0 - T_A}{10K}} \cdot K_i^{\left[1 - \left(\frac{I_A}{I_R}\right)^2\right] \cdot \frac{\Delta T_0}{10K}} \cdot \underbrace{\left(\frac{U_A}{U_R}\right)^{-n}}_{K_V}$$

WITH TYPICAL VALUES:

T_0 = 105°C	$I_A > I_R$:	K_i=4
	$I_A \leqslant I_R$:	K_i=2
T_0 = 85°C		K_i=2

ΔT_0= depending on the series: 3,5~10K, see databook value

$$0{,}6 \leq \frac{U_A}{U_R} \leq 1 \rightarrow n = 2{,}5$$

$$0 < \frac{U_A}{U_R} < 0{,}6 \rightarrow K_V = \left(\frac{U_A}{U_R}\right)^{-n} = 3{,}59$$

For $U_R \leqslant 160V$, Radial and SMT

$$\frac{U_A}{U_R} > 1 \rightarrow K_V = 1$$

OUR SNAP-IN IN RELATION TO ONE ANOTHER

SNAP-IN 85°C



SNAP-IN 105°C/ 125°C

