PTR HARTMANN
A Phoenix Mecano Company



Highlights	
2 to 12 poles	
2 and 3 pole modules	
Spacing 7.62 mm	
Lift type	
Wire entry parallel to PCB	
24 A with 2.5 mm² wire	
Wire Sizes	
Solid min	0.2 mm²
Solid max	4.0 mm²
Stranded (flexible) min	0.2 mm²
Stranded (flexible) max	2.5 mm²
Stranded with ferrule min	0.25 mm²
Stranded with ferrule max	2.5 mm²
Dimensions	
Stripped length	8.0 mm
PCB hole diameter	1.3 mm
Materials	
Clamp	Brass
Screw	Steel
Solder tab	Copper Alloy
Insulating Material	
Material	PA 6.6
Flammability class	UL 94 V-0
Temperatures	
Operating temperature	-40 °C (without mech. load) - 105 °C
Store temperature	-40 °C - 105 °C
Wave Soldering Process	
Soldering temperature, recommended	260 °C
Peak soldering time, recommended	3-4 s

Spacing 7.62 mm

Reflow Process

Soldering temperature, recommended	-
Peak soldering time, recommended	-

Colours

GREEN, RAL 6018

BLACK, RAL 9011

PEBBLE GREY, RAL 7032

BLUE, RAL 5015

LIGHT GREEN, similar RAL 6018

Colours according to RAL, there may be variations on colour due to production conditions.
Special colours on request.

Ratings

		c UL us			VDE	
UseGroup	B	C	D			
Rated voltage	300 V	150 V	300 V		750 V	
Rated current	20 A	20 A	10 A		24 A	
Rated wire size				min		max
- solid	AWG 30-12	AWG 30-12	AWG 30-12	0.5 mm²		4.0 mm²
- stranded	-	-	-	-		-
- stranded (flexible)	AWG 30-12	AWG 30-12	AWG 30-12	0.5 mm²		2.5 mm²
Torque	0.45 Nm	0.45 Nm	0.45 Nm		0.50 Nm	
Screw size	M3	M3	M3		M3	
Test voltage	1.60 kV	1.30 kV	1.60 kV		3.0 kV	

Accessoires

Figure	Designation	Article Number
	Bridge, 2-pole, insulated, BRI/2-7.5/7.62-L8.2-LIGHT GREY	Art.-Nr. 50000000017
	Screw Cover SC-AK700-YELLOW	Art.-Nr. 50700000004

PTR HARTMANN
A Phoenix Mecano Company

Spacing 7.62 mm

Order Data (Spacing 7.62 mm)

Number of Poles	Width (mm)	Article Designation	Article Number	PU
2	15.84	AKZ710/2-7.62-V-GREEN	50710020213 E	100
3	23.46	AKZ710/3-7.62-V-GREEN	50710030213 E	100
4	31.08	AKZ710/4-7.62-V-GREEN	50710040213 E	100
5	38.70	AKZ710/5-7.62-V-GREEN	50710050213 E	100
6	46.32	AKZ710/6-7.62-V-GREEN	50710060213 D	50
7	53.94	AKZ710/7-7.62-V-GREEN	50710070213 D	50
8	61.56	AKZ710/8-7.62-V-GREEN	50710080213 D	50
9	69.18	AKZ710/9-7.62-V-GREEN	50710090213 D	50
10	76.80	AKZ710/10-7.62-V-GREEN	50710100213 D	50
11	84.42	AKZ710/11-7.62-V-GREEN	50710110213 D	50
12	92.04	AKZ710/12-7.62-V-GREEN	50710120213 D	50

Technical drawing

